



SCHULICH
School of Engineering

Development of an Automated Monitoring and Control System for Construction Sites

Prepared by: Reza Maalek

Supervisor(s):


Prof. Janaka Ruwanpura

&

Prof. Derek Lichti

June 2015


Problem Statement




- Current Monitoring Practices are mostly Manual [1] :
- **Safety** → Risks of most common site accidents are not decreased [5]
- **Productivity & Communication** → 40-60% of tool time is wasted [6]
 - Untimely identification of causes of **delays** and **cost overruns** [2]
- Site supervisors spend **30-50%** on analysing the data [3 & 4]

Research Objective


- To Automate the Monitoring and Control Process
 - Automated Monitoring to determine:




Overview of LiDAR





Research Method



3 Main Questions






Automated As-built Model Generation




2. As-built Model Generation

- a. Point Cloud Classification
- b. Point Cloud Segmentation
- c. Boundary Detection
- d. Data Summarization and Intersection

2a. Point Cloud Classification: Planes



2a. Point Cloud Classification: Lines



Reality

Due to data artifacts caused by:

1. Occlusions
2. Moving objects
3. Dust


Outliers are present in the data

Classical PCA is very sensitive to outliers [6, 7, 8, 9]


→ Searching for a Covariance estimation Robust to outliers

- Minimum Covariance Determinant (MCD) [8, 9, 10]

Mixed Pixel




2b. Point Cloud Segmentation




Complete Linkage

Within the Attribute Space:



No prior knowledge of the number of clusters


2c. Discontinuous Surfaces




Use the “Modified Convex Hull” algorithm

Boundary Point extraction

Modified Convex Hull algorithm:




2d. Vertices and Intersection



Experiment 1: Laboratory


Testing the proposed method in a highly occluded area:

- A set of LiDAR data was collected using Leica HDS6100




Removing Floor and Flat Slab Ceiling

- To improve Calculation time:



Results




Floor Precision = 91.5%
Ceiling Precision = 92.5%


Recall=100%

**Accounting for more than
half of the points**

Experiment 1: Robust Segmentation




**95% of the points
correctly segmented**




**30% improvement to current
available method**


Experiment 1: As-built Model



Registration?




As-built Model



As-planned Model

2 Metrics for every point



Experiment 1: Results


Accuracy Assessment:

XRSE = 7cm

YRSE = 6cm

ZRSE = 1.2cm

MRSE = 9.4cm



Dimension Compliance Control of Walls:

Horizontal Direction = 7.5cm

Vertical Direction = 2.4cm

As-built vs. Total-station

→ **MRSE** = 0.7 cm


→ **9.4 cm is the errors during construction**

Experiment 2: Construction Site

Graduate Student Hall of Residence Project:




150 million points from 4 scan-stations




Experiment 2: Robust Planar Segmentation

**Using Region Growing
and Classical PCA**




**Planar Segmentation:
73% Accuracy**

**Using Our Robust
Method**




**Planar Segmentation:
95.2% Accuracy**

Experiment 2: Robust Linear Segmentation



**Linear Segmentation:
91.4% Accuracy**


Experiment 2: As-built modelling of Elevator shaft



Contractor suggested tolerance of ± 2 cm


Future Work: Progress Monitoring

Graduate Student Hall of Residence Project:



Future Work: Dimension Compliance

Taylor Institute of Teaching and Learning Project:



Contributions

- Fully Automated Monitoring and Control Process
- Automated As-built Model Generation Process
- Novel Robust Planar and Linear Classification Method
- Novel Robust Planar and Linear Segmentation Method

Construction Industry benefits:

- Reducing monitoring **time, cost and quality**
- Reducing rework due to poor quality
- Reducing construction claims and disputes
- **Quality assurance**, and **dimension compliance control**

Thank You for Your Attention

Questions?

References

1. Maalek, R. and Sadeghpour, F. (2011), “A Comparative Overview of Radio Frequency-Based Technologies Applicable to Locating Resources on Construction Sites”.
2. Semple, C., Hartman, F. T., and Jergeas, G. (1994), “Construction claims and disputes: causes and cost/time overruns”.
3. McCullouch, B., (1997), “Automating field data collection on construction organizations”.
4. Golparvar-Fard, M., Feniosky, P. M., and Savarese, S. (2009), “D⁴AR - A 4-dimentional augmented reality model for automating construction progress monitoring data collection, processing and communication”.
5. Maalek, R. and Sadeghpour, F. (2014), “Accuracy Assessment of Dynamic Resources on Construction Sites”, Automation in Construction (in-press)
6. Serneels, S., and Verdonck, T. (2008), “Principal Component Analysis for data containing outliers and missing elements”.
7. Stanimirova, I., Daszykowski, M., and Walczak, B. (2007), “Dealing with missing values and outliers in principal component analysis”.
8. Hubert, M., Rousseeuw, P. J., and Verdonck, T. (2012), “Deterministic algorithm for MCD”.
9. Nurunnabi, A., Belton, D., and West, G. (2012), “Robust segmentation for multiple planar surface extraction in Laser scanning 3D point cloud data”.
10. Rousseeuw, P. J., and Driessen, K. N. (1999), “A fast algorithm for the Minimum Covariance Determinant Estimator”